

THE SIMPLER, BETTER, FASTER WAY TO INCREASE PROFITS

For years, the Vitality Express® juice beverage dispensing system has answered operator's needs for increased sales and profitability. Quite simply because the Express is the most efficient, reliable and easy-to-use juice beverage dispensing system available. Operators around the world have come to rely on the Express program with its state-of-the-art dispensers and highest quality beverages, to serve more patrons profitably.

The Express II dispenser offers many features and benefits to your operation.



Full of Options

- Three unique touch-button models are available: Press and Hold, Portion Control for 1 serving size and Portion Control for 3 serving sizes.
- Lower Maintenance drip tray
- Security lock. All Vitality® dispensers can be key locked. Also equipped with a special dispense switch which turns off the pumping mechanism and graphics panel light.

Safety First

- The unique Express design makes it the safest, most sanitary juice dispensing system in the industry.
- No tubes or hoses that can trap and hold bacteria.
 - It is a completely closed system which protects the juice from exposure to air and internal parts, eliminating the possibility of contamination.

Innovative Packaging

The Express Pak® dispenser cartridge has patented features not found in other beverage systems.

- Patented Express Pak pump nozzle perfectly blends concentrate and water for consistent quality with every serving.
- The cartridge is self-venting with no vent tabs to remove.
- The entire cartridge, including the pump, is disposable and recyclable.



Popular Flavor Varieties

The Express Pak is available in a variety of juice flavors, including traditional flavors like 100% Valencia orange juice, apple juice, lemonade, and punch, as well as specialty flavors like calcium-added orange juice, citrus peach, passion-orange-guava and many more.

THE VITALITY EXPRESS® BEVERAGE SYSTEM

SPECIFICATIONS	2-DRINK BEVERAGE SYSTEM
Dispenser dimensions	
Height	29.3" (74.4 cm)
Width	9.0" (22.9 cm)
Depth	24.3" (61.7 cm)
Type	Post-mix-refrigerated concentrate and water mixed on demand.
Pump	Two electronically controlled pump motors with individual pressure regulating valves for water.
Product flow rate	Approximately 1.3 oz/second (38.5 ml). Varies with product.
Concentrate capacity	Approximately 405.6 oz (12 liters) i.e. Four separate packages of 101.4 oz (3.0 liters) each.
Product capability	Two juice selections offered.
Electrical system	Printed circuit board with integrated electronics and self-diagnostic system.
Security system	Key lock located on side of door. Dispense switch located behind graphics panel turns off water solenoid, pump motors, and turns off graphics panel.
Refrigeration system	Dual capillary tube refrigeration system with individual controls for water chilling and concentrate cooling. Temperature is controlled by electronic thermistors for accuracy.
Capacity	Five 5oz. (148 ml) servings per minute under 45° F (7.2° C) at ambient and incoming water temperature of 75° F (23.9° C).
Water connection	3/8" (0.95 cm) outlet hose fitted with 3/8" male flare.
Water supply pressure	Requires 30-100 PSI.
Approvals	UL, C-UL, NSF, TUV, GS
Shipping weight	120 lb. (54.6 kg)
Clearance	2" (5.08 cm) at rear for ventilation.



VITALITY, VITALITY EXPRESS and VITALITY EXPRESS PAK are registered trademarks of Vitality Foodservice, Inc.

©2005 Vitality Foodservice, Inc. All rights reserved.



A Refreshing Approach to Beverages

400 N. Tampa Street · Suite 1700 · Tampa, FL 33602
 (888) 863-6726 · Fax: (813) 301-4770
www.vitalityfoodservice.com